



2018

RULE BOOK

INDEX

| <u>Topic</u> | <u>Page</u> |
|--------------------------------|-------------|
| Rule Book Disclaimer | 3 |
| General Track Rules | 4 |
| Protest Rules | 10 |
| Safety Rules | 10 |
| Flags | 11 |
| Super Street Class | 12 |
| Limited (B Mod) Modified Class | 18 |
| A-Modified Class | 25 |
| Sprints | 39 |

RULE BOOK DISCLAIMER

The rules and/or regulations set forth herein is designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the conditions of all events, and by participating in these events, all participants are deemed to have complied with these rules. No expressed or implied warranty of safety shall result from publications of or compliance with these rules and/or regulations. These are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator, or official.

The race director shall be empowered to permit reasonable and appropriate deviation from any of the specifications herein or impose any further restrictions that in their opinion do not alter the minimum acceptable requirements. No expressed or implied warranty of safety shall result from such alteration of specifications. Any interpretation or deviations from these rules are left to the discretion of the on track officials.

THEIR DECISION IS FINAL!!

ABSOLUTELY NO ONE under the age of 18 (eighteen) years of age will be allowed in the pit area without the written consent of a parent/guardian and then they **MUST HAVE A PAID PIT PASS.**

Track Admission:

Grandstands - Adults \$12.00—Kids 12 & Under are Free

Pit Pass—Adults \$30.00 — Kids ages 4 to 12 are \$15.00. Pit Pass armbands must be worn by kids and adults all night and must be on the person signed in. If you are caught without an armband you will be escorted to the pit gate to pay. 2nd time you are caught you will not be allowed in the pit area again.

ABSOLUTY NO REFUNDS WILL BE ISSUED.

St. Francois County Raceway warns everyone racing is dangerous. You could be injured or killed, even though we carry insurance – Participate at your own risk!

Any Specifications not discussed in these rules whose legality is questionable will be considered illegal until approved by track officials.

REMEMBER, RACING IS FUN!!!!

GENERAL TRACK RULES

RACECEIVERS ARE REQUIRED IN ALL CLASSES

1. Initial **START** will begin at the white line between turn four and the main flag stand. You cannot pass until your car passes the cone. **If all running cars have completed one (1) full lap and have been scored it is considered a completed lap (first lap). Only the leader must be scored to complete any further laps including the checkered flag. Split-yellows will be used for scoring, cars crossing the start-finish line before yellow is displayed will be scored on that lap and aligned accordingly. All cars not having crossed the line will revert to the previous scored lap and aligned accordingly.**
2. **There will be a DRIVERS MEETING every week at 5:30 pm in front of the Pit Concession Stand.**
3. At the start of the race, **all starts will take place at a CONSISTENT SPEED, with no brake checking/dragging the brake. Nose-to-tail. Starts will take place within the designated area (cones and/or lines). Any car out of line, passing before designated area, or jumping start will result in a yellow flag and the whole roll will be moved back one row. Second violation will move car to rear, third violation disqualified. If car starts on last row, second violation will result in disqualification.**
4. Once a race has completed one (1) full lap and a caution occurs, restart will be done **Delaware double file restarts. Leader will be out in front by their selves. Second place will choose inside or outside. Once second place decides where they are starting the rest of the field will follow suit.**
5. Cars not taking green flag to start the race will not be allowed on the track.
6. **We will not wait on anyone to get on track. If you come on track and don't attempt to line up in your position, officials will assume you want to start at the rear, if you haven't already let officials know before race.**
7. **If we have to stop the race due to a car malfunction issue you will be charged with a caution. OFFICALS decision.**

Any car stopping on the track **or involved in a wreck** will be put in the rear and charged with a yellow. If you stop to avoid a spinning car or wreck and are not involved in the wreck you will get your spot back. **If you stop under caution at an official to argue about your line up, you will be put to the rear of the field. If you stop for a safety issue, you will be able to maintain your**

spot.

1. **Any car that spins, involved in incident and/or has problem but does not bring out a yellow will blend back into the field where the driver is able. If the yellow comes out (Inadvertent Caution), officials will determine the placement of the cars involved. Placement will be where car blended back into the field if able to determine or realigned according to last scored lap.**
2. **If you are racing and cause another car to spin/stop on track, you will be charged the yellow and sent to the back. Black flags will be given for retaliation, rough driving, or un-sportsman like conduct.**
3. **If driver will not get in position/stay in position under caution, car will be sent to the rear at OFFICIALS decision.**
4. When a caution occurs on track, all drivers will slow, remain in position.
5. **Race is complete when the leader receives the "Checkered Flag" at officials discretion. If yellow flag comes out, races is scored on last lap.**
6. **When a caution occurs all lap cars will be put to the back in all classes. A car going to the rear for causing a caution may be realigned ahead of a slow/multiple lap down competitor.**
7. **Cars judged by officials to have intentionally caused a yellow flag may be disqualified from that race. "Causing a caution because you got a bad start"**
16. All red flag lineups will go to the last completed green flag lap.
17. **There is a (1) one minute per lap time limit for each class. Red Flag conditions will not count against time limit. (example : 6 lap heat race will have 6 minutes to complete heat race. A 25 lap feature will have 25 minutes to complete feature.) The next flag that comes out will complete the race once the time limit is met.**
18. **NO ONE IS ALLOWED ON THE TRACK EXCEPT TRACK OFFICIALS, OR WITHOUT THE PROPER TRACK CREDINTALS. NO EXCEPTIONS!!!!** Anyone caught on the track could result in removal from the pit area.
19. Any driver leaving their car to argue with official on or off the track can be barred for (2) two race nights. Decision will be made from that official and track owner.
20. Drivers are responsible for their pit crew.
21. Any threatening from the driver, crew member or fan toward any other driv-

er, track official or fan will be escorted from the premises immediately.

22. Any physical contact from the driver, crew member or fan toward any other driver or track official will be suspended for 2 weeks or indefinitely.
23. If you are involved in a wreck you must stay with your car to help. If you leave your car it will be taken to the infield and left until it is convenient to get car back to the pit area.
24. All classes may go off the track on a yellow caution and change a flat tire/ make repairs in the designated location and may return on the track before the green flag is dropped.
 - Sprints designated locations will be on the orange concrete pad by the exit at turn #3.
 - A- Modified's , Limited Modified's and Super Streets designated location is at the scales

Car must return on track before green flag is dropped again, we will not wait on driver.
25. Anyone leaving the track for any reason and returning to the track in that race must go to the rear of the field.
26. No working on cars on the track except on open red flag conditions. Wait for pit steward to give the okay to go on track. Any person caught on the track attempting to work on a car under a closed red flag will be removed along with the driver and car.
27. No one is allowed on track surface. No one is allowed to touch or work on a car at any time, unless an open red occurs.
28. All cars that change a flat tire on a Red must go to the designated work area to change a tire and they must go to rear of field. If a tire is changed on the track then the car is disqualified.
29. Any car going to the work area will be given 3 minutes to return back to the track, only on the first lap of any race. After the completion of lap one, courtesy laps will only be given until lineup is correct. You must change a flat tire at the designated work area.
30. Any cars lining up by turns 3 and 4 must line up behind the orange cone. Any car lined up in front of the orange cone will have to start in the back of that race. (This is for the safety of the drivers and officials).

31. Courtesy Rule: Any car from another track with minor rule differences may at official's discretion, race on that night but will be notified of any modifications and will have to be legal on the next visit to the track.
32. All Points go to the driver (Not the car). If you are driving for someone else, you **MUST** tell the girls at the pill draw window & the pit steward, if not you will not receive any money or points.
33. Anyone changing cars or drivers from heat to feature race will start on the rear of the field. Both the car and driver must be a qualified for that nights feature. If it is not a qualified car/driver then you must run the semi. Anyone changing must notify officials or they will be disqualified.
- 34. ALL RULES ARE ENFORCED BY TRACK OFFICIALS AND ARE FINAL AND WILL NOT BE CHANGED BY PROMOTER!!!!**
35. Any incident or occurrences not covered in these rules will be ruled upon by the track officials after all races are finished.
36. St. Francois County raceway assumes no responsibility for damage to or loss of your equipment, vehicles, or any parts whatsoever. No personal vehicles are allowed in the pit area, except what is hooked to a race trailer.
37. The management reserves the right to change the race program or rules at any time to improve the racing program.
38. Pill draw for all classes will be from 4:30 -5:30 pm. Persons drawing pill must sign by the pill draw number they get. If you are not there by 5:30 pm to draw your pill you will be put on the back of the heat. If you draw 2 pills you will receive the highest number you draw out. If you are running late you can call the track and they will draw a pill for you. Track phone is (573) 756-9248.
39. Drivers may pick up their winnings starting after the Sprint Feature and until 15 minutes after the last race is completed.
40. You **MUST** sign a receipt for points and money at pay window. If any driver or crew member argues or uses fowl language with the ladies at the window your money and points will be held till track promoter talks with you.
- 41. All checks must be picked up within 30 days or they will be voided.**
- 42. Any lost check that has to be written again will have \$35.00 withheld from the amount to cover stop payments.**
- 43. Any checks not cashed by December 1st will have a stop payment done on**

them.

44. **Driver form must be completed and have Tech Signature on it and turned in. Checks will be held until a completed driver form is turned in. (NO EXCEPTIONS)**
45. **Pad rental is due by the 1st night of racing. If not paid in full by the 1st night of racing your payout checks will be held to cover pad rent. If your payout check is not enough to cover then we will continue to hold checks till balance is paid in full.**
46. Top 2 cars in each heat, semi and dashes must weigh after each race. Top 5 in feature must weigh after the feature race; go directly to scales after your race if you pass up scales you will lose points & money for that race.
47. If you do not weigh after the feature, everyone after that spot will be moved up a position.
48. First offense for aggressive driving you will be charged with a yellow and sent to the rear. Second offense for aggressive driving you will be charged with a black flag and you and the car are done for the night and the driver will lose all points and money.
49. For over aggressive driving you will be black flagged and you and car are done for the night and will not receive any points or money. Call will be determined by track official on over aggressive driving.
50. Any driver slamming into another car during a yellow flag or after the race will be disqualified for that race and will not receive any point or money for that race.
51. Lineups will be posted. It is the driver's responsibility to be lined up in his proper position prior to the finish of the proceeding race.
52. If the leader takes the checkered flag and wreck occurs, then the cars will be scored as they pass the finish line. If a wreck occurs before the leader takes the checkered flag, then it will go back to green, white, checkered.
53. Points will be given for the heat, dash, and feature in each class.
54. If we get rained out or any other uncontrollable occurrences happens (electric outage, fire, etc.) in the middle of the race program, and all dash races are ran, then it is considered a full night and features will be made up another night.

55. Any points race ending in a tie will be determined by the most feature wins. If there is no feature wins then it be determined by the most seconds, then thirds and so on.
56. If the last points night is rained out, then points are determined by the finish of the previous race night.
57. If you have a problem or you think something is not right, you need to go to the promotor and see what can be worked out to solve the problem. It takes the drivers, fans, pit crews, & family to make a great track work.
58. All drivers, pit crews and fans must wear a shirt & pants at all times.
59. If you get into a fight before, during or after the races you will be kicked out for 2 race nights. Second offense you will be out the rest of the year.
60. The pit area must be cleared within 60 minutes of the completion of the race program for insurance purposes. **NO ONE IS ALLOWED ON THE TRACK AFTER THE RACE PROGRAM IS COMPLETE. NO EXCEPTIONS!**
61. Only one vehicle per race car is allowed in the pit area. No personal vehicles without a permit.
62. One ATV is accepted for each race car, anyone speeding through pit area will lose ATV privileges for the year. NO JOY RIDING IN THE PIT AREA ESPECIALLY KIDS. **All ATV's must have a permit. All ATV's must have an orange flag attached.**
63. If any driver gets into a FIGHT at our Annual Race Banquet, He/She will not be allowed to race for the first two (2) races of the next season.

PROTEST RULES

1. Cars may be inspected at anytime by track officials.
2. All protests must be made to your pit steward within 5 minutes after the feature race is completed. The driver must have the correct amount of cash in his possession.
3. Quick-change gear ratio \$50.00.
4. If you are protested & do not tear down, you will be disqualified and suspended for two (2) race nights and lose all money and points for that night. If you are protested again and you do not tear down, you will have to move up to the next class.
5. Only cars which finish on the same lap and in top ten positions of the feature race will be allowed to protest. The race team protesting will be allowed the driver and one member of its crew. The race team that is being protested will be allowed the driver, the owner and up to two crew members. Only those people and track officials will be allowed. All final results of protest will be announced that night and next night of racing.
6. Only the driver of a race car will be allowed to protest another car.
7. The protest car must be torn down on that race night.

SAFETY RULES

1. There will be no drinking of alcoholic beverages and/or use of any controlled substances in the pit area before, during, or after the race program. Anyone deemed under the influence of alcohol and/or a controlled substance, or having either in their possession, will be immediately suspended. In the event of a violation of a controlled substance, the proper authorities will be notified.
2. All drivers in all classes must wear a full fire suit and approved helmet (full face helmets only!!!!!! no open face helmets) and an approved 3-inch restraint system, which must be updated in 3 year intervals. Fire retardant gloves, shoes, socks, underwear and neck braces are highly recommended.
3. All cars must be equipped with approved fuel cells.
4. A minimum size of 16-inch numbers must be on each side of the car.

5. No two-way radios allowed in the pits or in cars.
6. **ALL CARS MUST HAVE A WINDOW NET OR USE ARM RESTRAINTS and at least 3 vertical bars in front of the driver.**
7. **WE STRONGLY URGE YOU TO WEAR NECK RESTRAINTS FOR YOUR SAFETY.**
8. Cars may be inspected by track officials.
9. Speed limit anywhere in the pits is IDEL SPEED only, for RACE CARS and ATV's.
10. No one is allowed to argue or discuss any item with track officials while a race is in progress. Abusive or improper language by anyone will not be tolerated. Any type of physical assault by anyone may result in arrest by a county deputy.
11. All weight must be painted white, have a car number on them, and bolted. No rearview mirrors will be allowed.
12. All cars must have a front and rear bumper at a reasonable height for pushing and must have a chain or steel loop device attached to the center of the chassis on the front and rear to provide wrecker hook-up.

FLAGS

1. Green flag and light means racing.
2. Yellow flag means caution, slow down immediately and maintain position.
3. Red flag means all cars must stop immediately. All cars go to the top of the track and stop. Anyone going to the pits during red flags will lose their position in the race.
4. Black flag means unsafe conditions (flat, excessive smoking, loose car parts, etc.). Cars will be warned with a black flag in case of minor incidents. Rough driving will result in immediate removal from the track for the remainder of that race. Anyone refusing to leave the track when there is a black flag will result in suspension of two nights.
5. White flag means there is one lap remaining in the race. Any yellow or red flag will be thrown at Flagman's discretion from this point on.
6. Checkered flag means end of race.

SUPER STREETS

(No Motor Claim)

All general rules apply

1. Any American Coupe or Sedan.
2. After market aluminum or steel bodies are legal.
3. Must have stock OEM or OEM style steel floor pan in stock location extending past driver seat. Firewall may be stock or constructed of minimum .049 steel and must be complete side to side.
4. Cars that do not have stock OEM or OEM style firewall and floor pan cars **must add 50 lbs. bringing total weight to 3,000 lbs. after race with driver.**
5. Frame must remain stock with a MINIMUM wheelbase of 101" with a 1" TOLERANCE from side to side.
6. Wheel base must match frame being used.
7. Fenders may be trimmed to allow for tire clearance.
8. Sub-frame cars may be tied together under the cars, front and rear bumpers in Stock position, and must be rounded off.
9. Must have chain on front for tow truck hook up. **MANDATORY**
10. Nose and grill may be replaced with plastic.
11. Nerf bars not to exceed 1 inch from body and maximum 1 1/2 inch diameter.
12. Fuel Cell is Mandatory. No boat tanks or homemade gas containers allowed. Trunk flooring may be removed to mount cell. Fuel cells **MUST** be contained in reinforced steel container and securely mounted.
13. Battery may be relocated, but not in driver's compartment. Only one 12-volt battery (no 16 volt batteries).
14. Doors must be welded shut.
15. All glass and flammable material must be removed.
16. **ALL CARS MUST HAVE A WINDOW NET OR USE ARM RESTRAINTS and at least 3 vertical bars in front of the driver.**
17. Cars must have a MINIMUM 6 point roll cage, 1 1/2 inch minimum diameter pipe with wall thickness of .095"inch, securely welded to frame. Three (3)

driver's side door bars required. NO BLACK or galvanized pipe.

18. After market pedals will be allowed **with cockpit adjustable front to rear brake bias**
19. Fiberglass hoods and roofs are allowed.

SUPENSION:

Front :

1. A-frames

- *Tubular adjustable or non-adjustable upper a-frames allowed.
- *Front lower control arms must be unaltered OEM or approved direct replacement. **Aftermarket bushings are allowed**
- *No aluminum parts.
- *Upper a-frame mount may be moved and replaced with aftermarket mount.

2. Adjustable weight jacks are allowed must be in original centerline of spring tower.
3. Only one shock per wheel.
4. Must be steel non-adjustable. No air remote reservoir, bulb type, or Schrader valve shocks allowed.
5. Shock location may be moved but frame cannot be altered in any way.
6. Right front safety hub is optional.
7. Engine set back - #1 spark plug hole can be no farther back than center of upper ball joint.

Rear:

1. Adjustable weight jacks mounted in original centerline of spring tower are allowed.
2. Adjustable shackles are allowed.

3. No bird-cages, no sliders, no traction devices of any kind, no lift bars etc.
4. Multi leaf stack springs are allowed, no mono-leaf's.
5. Composite leaf springs are allowed.
6. No Chrysler springs allowed except on Chrysler cars.
7. Trailing arms must be non-adjustable OEM or non-adjustable OEM direct replacement. **Aftermarket bushings are allowed**
8. Lower trailing arms must be at least 19" center to center and same length on both sides.
9. Front upper and lower trailing arm mounts must be in OEM unaltered location.
10. Rear upper trailing arm mounts can be altered to set pinion angle.
11. **Rear lower mounts on rear axle may be no more than 4" from bottom of axle tube to the centerline of bolt hole, must be same height on both sides.**
12. No suspension limiting devices (chains, straps, etc.)
13. No pull bars, or J-bars allowed

REAR ENDS:

1. Rear end must be locked or posi-trac. 8" or 9" Ford may be used on all car makes.
2. Floater rear ends are allowed.
3. No traction control devices.
4. No ratchet rear ends or torque dividing differentials.
5. Rear disc brakes are allowed

STEERING:

1. Must be OEM and remain within the original bolt pattern for frame being used.
2. May be modified to suit driver, but must remain on left side of cockpit.
3. Quick steer is allowed.
4. OEM rack and pinion steering allowed if car was originally equipped. No

aftermarket rack and pinion units.

TRANSMISSION:

1. Three or four speed OEM transmission allowed.
2. Automatic transmissions are allowed.
3. Cars must move under it's own power and must be able to engage all gears while engine is running.
4. No direct drives, or five speeds, "in and out" boxes, or quick change devices.
5. Cars must have a workable clutch. Mini clutch is allowed.
6. Bert or Brinn type transmission are allowed
7. Manual transmissions including bert/brinn type must have explosion proof steel bell housing covering a minimum of 270 degrees around top of clutch/ flywheel area.
8. Automatic transmissions must have original bell housing with an approved scatter shield constructed of minimum 0.125" inch by 3" inch steel strap 270 degrees around flex plate.
9. Driveshaft must be a minimum of two (2") inch diameter and made from magnetic steel.
10. The driveshaft must be painted white and clearly labeled with car number on white portion of driveshaft.
11. A 360 degree drive shaft loop REQUIRED. Must be constructed of at least 0.25" inch by 2" inch steel or 1" inch diameter tubing mounted 6" inches behind the front universal joint.

WEIGHT:

1. Cars must weigh 2950 lbs. with driver after races. All weight must be mounted with (2) ½" bolts and painted white with the car number clearly marked.
2. Cars with unapproved floor pan/firewall must weigh 3,000lbs.

TIRES:

1. Any 8" modified tire or 10" asphalt take offs. Tire must match wheel width.

Grooving and siping is allowed. All tires must durometer a minimum of 50 hardness. Softening is not allowed. Solvents of any kind are not allowed.

- 2. All tires must "cold" durometer a minimum of 50 prior to pre-race inspection, no tolerance allowed. After any race the tires must "Hot" durometer 45 or above. Any tire reading below 50 "Cold" or 45 "Hot" will result in a disqualification**
3. 8 or 10 inch steel wheels, bead lock allowed on right front & right rear only.
4. 1 inch lug nuts are MANDATORY.

FUEL:

1. Straight Racing gas, E85 and pump gas permitted. No nitrous oxide or alcohol.
2. Cars must have a fuel shut off that driver can reach when in car.

ENGINES:

1. Steel blocks only must be able to be used in a conventional passenger car without alterations.
2. 23 degree cast iron heads only.
3. Aluminum intakes are allowed.
4. Oil pump must be in stock location and OEM.
5. No dry-sump systems.
6. No aluminum oil pan.
7. Any camshaft is allowed.
8. HEI STYLE distributor or MSD boxes are allowed.
9. Aftermarket or OEM Distributors are allowed.
10. No adjustable timing control or magnetos allowed.
11. One MSD box allowed.
12. Aftermarket ignition module or coil allowed.
13. Track may confiscate and exchange MSD box at any time.

14. Magnetos and/or crank triggered ignitions are not allowed.
15. No more than one (1) coil may be used.
16. Kill switch required within easy reach of the driver. The switch must be clearly marked "off" and "on" Ignition box must be mounted out of reach of the driver.
17. Carburetors spacer NOT exceeding 2 inch IN HEIGHT.
18. Mechanical fuel pump in stock location. Stock manual fuel pump. No electric or belt driven pumps.
19. Headers or exhaust manifolds allowed. NO. 180 degree headers. No tri-y headers. Exhaust must be mounted in such a way as to direct spent gasses away from the cockpit.
20. Carburetor can be NO larger than Holley 500 CFM 2 barrel & must pass inspection from top side with gauge. (Must have throttle bore no bigger than 1.688" inch).
21. Choke horn may be removed.
22. Rochester & Motor Kraft are legal.
23. No aerosol carbs are allowed.
24. All cars must have a working starter and must have the capability of starting without being pushed or pulled.
- 25. Mufflers is Mandatory! 6" SLIP ON STYLE OR EQUIVILANT**

ALL GENERAL RULES APPLY

LIMITED MODIFIED (B MOD) CLASS

1. **ROLL CAGE:** Must consist of continuous hoops, minimum 1.50-inch O.D. tubing, with a minimum wall thickness of .095-inch for main cage, frame-mounted in at least six places, low carbon or mild steel recommended. Must consist of a configuration of front, rear and top hoops connected by tubing on sides or side hoops. Driver's head must not protrude outside cage with helmet on. Roll cage must be securely supported and braced with minimum one cross bar in top halo. Foot protection bar required. Main cage no further forward than the rear of the engine. All bars forward of cage must be lower than hood.
2. **DOOR BARS:** All driver's side door bars and uprights must be minimum 1.5-inch O.D. and .083-inch wall thickness. Minimum three driver side door bars, parallel to ground and perpendicular to driver, and welded to front and rear of roll cage, passenger side must have at least one cross door bar, horizontal or angled, minimum 1.25-inch O.D. & .083 inch wall thickness, and one top door bar, minimum 1.5 inch O.D. & .083 inch wall thickness, steel door plate 18 gauge or .049-inch minimum thickness, must be securely welded to outside of driver side door bars and cover area from top door bar to bottom door bar and from rear hoop down post to 5 inches in front of **seat. MUST BE VISIBLE FOR INSPECTION.**
3. **SAFETY:** Rules apply at all times while car is on track. Snell rated SA95 or SA2000 helmet are required. SFI approved full fire suit, gloves and shoes required. Fire retardant head sock and underwear, head and neck restraints are recommended. Driver side window net or arm restraints required, and must be mounted so latch is at top front of window or arm restraints. Minimum three - inch wide five - point safety belt assembly required. Must be mounted securely to roll cage, recommended to be no more than three year old. Kill switch required within easy reach of driver and must be clearly marked 'OFF' and 'ON'. A small Fire extinguisher in driver's compartment is mandatory.
4. **FRAME:** OEM complete 1964 or newer, perimeter American rear-wheel drive passenger car frame only. No sports car frames. Frames must be full & complete, cannot be widened or narrowed, and must be able to support roll cage on both sides, except weight jack in original center line of spring tower allowed: frame may be cut a maximum 36 inches forward from center of rear housing: horns may be removed in front of steering box: front cross member may be notched and boxed for radiator and/or steering clearance:. Maximum seven inch wide opening in side of spring tower for spring removal. Maximum

two inch wide by four inch tall frame stiffener may be welded directly to outside of left side frame rail. Minimum wheelbase is 108 inches, maximum is 112 inches, both sides. Maximum overall width (front or rear) shall not exceed 78 inches from outside of tire. No part of frame can be lower than four inches from ground except front cross member.

5. **BODY:** Must be same width, front to rear, and parallel to OEM frames. Engine compartment must remain open (no side panels). Hood must be enclosed at rear, no panel in front of right door to engine compartment. No inner panels, No car covers. Must have front windshield and rear window support posts. Driver and passenger side windows must have at least 12-inch opening, measured at center of window, between lowest point at top of window, whether roof or roll cage, and highest point at bottom of window, whether interior or body. May use Lexan in sail panels, may use full windshield. Must be fiberglass or aluminum full size roof rounded in all directions. (roof escape panel is allowed) plastic skirting allowed on bottom of doors and quarters. Outside of tires must be widest part of car. 5" spoilers allowed. Spoiler supports no more than 5" tall in rear, 2" tall in front, and 12" long.
6. **DRIVER COMPARTMENT:** Must have a minimum three windshield bars in front of driver. Lexan or aluminum cowl panel in front of driver can be no wider than cockpit and no farther back than steering wheel. Minimum .125-inch aluminum, or .060-inch steel, complete floor pan required. Aluminum high-back seat only and must be bolted in next to left side frame rail and ahead of rear tires. Bottom of seat can be no lower than bottom of frame rail. Driver must be sealed off from race track, driveline, engine, fuel cell, canisters and pumps. Accumulators cannot be mounted between driver and left-side door bars. No devices that would enable driver adjustment to alter wheelbase or for weight jacking while car is in competition. No mirrors or reflective sun visors.
7. **FRONT SUSPENSION:** All components must be steel, unaltered OEM, in OEM location and replaced by OEM parts, except tube type upper A-frames with or without aluminum/steel cross shaft & mounts can be moved. OEM replacement lower A-frames bushings only, no offset or bearing type. All lower A-frame mounts and bolt holes on frame must be in stock location. Lower A frame must be right & left and of same design; rubber, nylon, or steel lower A frame bushings, no offset or bearing type: welded or bolted shock mount on lower A frame. Lower A frame mounts & bolt holes on frame must be in

OEM, location. OEM ball joints only. Sway bar must be unaltered OEM. After market lower A-Frames are legal.

8. **STEERING:** All components must be steel, unaltered OEM, in OEM location. except outer tie rod end & adjustment sleeve may be replaced by a minimum .625-inch steel rod end and steel tube; spindles can be ground for brake caliper clearance only; spindles must be right and left, and of the same design; bolt on spindle savers allowed; steel steering shafts and knuckles only. Steering quickener, steering wheel and quick release may be aluminum. Cockpit steering may be modified, must be kept on left side. No rack and pinion.
9. **SHOCKS:** One steel non-adjustable unaltered shock per wheel. One additional shock allowed on rear suspension. No bumpers or stops, no threaded body, front coil over, air or remote reservoir shocks. Front half may be shielded. No Schrader valves.
10. **SPRINGS:** One steel, non progressive coil over spring and/or steel leaf spring per wheel only. One additional spring allowed on pull bar or lift bar, may be progressive. Any coil spring must be at least 4.5 inches O.D. No torsion bars or air bags.
11. **REAR SUSPENSION:** All components must be steel. No covers allowed. Any 3 link or 4-link suspension allowed. All trailing arms/link bars must be steel tubing. Rear of frames may be altered to accept leaf or coil springs. Steel coil over eliminators or steel/aluminum coil over kits allowed. Must conform to shock and spring rule. One mechanical traction bar (pull or lift bar not both).
12. **REAR END:** Any steel approved OEM passenger car or truck rear end allowed. Safety hubs (floater) allowed. All components must be steel, except lowering blocks, axle cap, and drive flange. Inspection hole in housing is required. Full steel spool, steel mini spool or welded rear ends only. Steel axles only. Quick change rear-ends are allowed, must claim the gear ratio you are running and cannot change ratio during the night. Track can inspect gear ratio at any time. A gear can be changed if damage is suspected but must be approved by track official and replacement gear must be same ratio that was claimed at the beginning of the night. See protest rules. No cambered rear ends. One piece drive flange only. No torque dividing differentials.
13. **BUMPERS AND RUB RAILS:** Steel only. Bumpers must be used both front and rear at all times and welded or mounted with minimum .375-inch bolts. Must be minimum 1.25-inch O.D. tubing, .065 wall thickness on front, .095 wall

thickness on rear. Two-bar front bumpers must be mounted to frame-end to frame-end, no wider than width of material outside frame horns and with bottom loop parallel to ground. Top bar must be directly above bottom bar, minimum 6.5 inches apart, measured center to center. Rear bumper and nerf bars can be no wider than tires.

14. **TIRES AND WHEELS:** Note: **The 2018 regular track season will introduce M-30S, with a redesigned tread pattern. The HOOSIER A-40S, M-30S, G-60, American racer g-60 will be the only approved tires. The Hoosier H40 and M60 is approved as a right rear option. Grooving and siping will NOT be permitted on the M-30S, grinding is allowed. Grooving, sipping and or grinding of the A-40s, H-40, M60, and g-60 tires is allowed.** No re-caps. Aluminum or steel spacers only. May use I.M.C.A. approved bead lock, on right rear only. External, steel bead lock only and it cannot make wheel any narrower than 8 inches and no wider than 8.75 inches. Must use only steel bolts. Driver can run mud plugs on all 4 wheels. Rim-mounted bleeder valves allowed.
15. **BRAKES:** Must be steel approved OEM, operative four wheel, drum or disc. Must maintain OEM dimensions for Hubs/rotors and calipers, cannot be lightened. Bolt patten may be changed. Larger studs allowed. Rear rotors may be aftermarket, min. 0.810-inch thickness. Vented rotors only, no scalloped rotors. No brake shut-off or pressure sensitive devices. One proportioning device allowed, front to rear only. Brake lines must be visible.
16. **EXHAUST:** Round tube headers only. All primary header tubes must enter directly into one collector, at same point, at end of header. No exhaust sensors. **MUFFLERS ARE MANDATORY 6" SLIP ON STYLE OR EQUIVILANT.**
17. **FUEL SYSTEM:** Mechanical fuel pump only and must be mounted at front of engine. Racing fuel cell required, maximum 32-gallon capacity, must be in minimum 18-gauge steel container. Cell must be securely mounted behind rear axle, between rear tires, minimum of four inches ahead of bumper, minimum of ten inches above ground. Must mount with minimum two .125-inch thick solid steel straps, two inches wide around entire cell. All cell mounts must be steel, securely welded to frame/cage. Protective tubing must cover rear and extend past both sides of cell. No part of cell shall be lower than protective tubing. Fuel cell vents, including cap vent, must have check valves. Pick-up must be on top or right side of cell. Limit of one fuel filter. No cool cans. One naturally aspirated 2-barrel 500 cfm 1 3/8" venturi carburetor only. May remove choke horn. No aerosol carbs. Allowed.

18. **FUEL:** Must be Gasoline . NO performance-enhancing additives. Upper cylinder lube allowed. Fuel sample may be taken from any car at any time. Penalty for illegal fuel is disqualification from event and \$250 fine – first offense. No Alcohol. E-85 allowed.
19. **WEIGHT:** Minimum weight limit of 2,400 pounds with any motor, If you run aftermarket transmission (Bert, Brinn, etc.) add 50lbs 4-bar cars add 100lbs no tolerance, after race with driver in car. No weights and/or loose objects in driver compartment or outside body. Weights must be securely mounted to frame or roll cage and painted white with car number on it. Must be attached with at least two .5-inch bolts. No titanium, magnesium. No gun-drilled, tubular, hollow bolts or studs.
20. **BATTERY AND STARTER:** One 12-volt battery only, must be shielded and securely mounted between frame rails. Must have capability of starting without being pushed or pulled. Must leave initial staging area on demand, unaided, or go to rear of that race. Reverse-mount starters with OEM case transmissions only.
21. **GAUGES AND ELECTRONICS:** No transmitting or listening devices, timing retard controls, or digital gauges (including tach). No electronic monitoring computer devices capable of storing or transmitting information except along tach. No adjustable ignition control boxes. Only one 12-volt ignition box allowed, must be out of driver's reach. No additional ignition accessories allowed. Only change allowed to ignition box is one high-end rev-limiter setting. This setting can be changed through one chip only, or an internal setting inside box. No electronic traction control devices (\$10,000 fine).
22. **TRANSMISSION AND DRIVESHAFT:** Must have at least two forward gears & one reverse, plus a neutral position. With engine running and car in still position, must be able to engage car in gear and move forward, then backward. Three speed, four speed and automatic. No five speed (or more) transmissions, in and out boxes, or quick change devices allowed. Functioning shift levers must be in OEM location on all OEM production type transmissions. Flex plates must be full steel, unaltered OEM or OEM replacement. Flywheel/ flex plate must bolt to engine between clutch assembly an crankshaft and all driving components within bell housing must rotate while car is in any gear. Transmissions must be one of the following designs:
 - MANUAL:** Must have a standard OEM case & working disc-type clutch or approved cone or disc type coupler inside an explosion proof steel

bell housing. One fly wheel only, minimum 8.5 inches diameter. Diameter of clutch disc must be a minimum of 5.5 inches. Clutch assembly must be steel, except housing, which must be steel and/or aluminum. Bell housing can have only a hole for throw out bearing lever or hose, must be 270 degrees around top of clutch and flywheel area. Standard or reverse mount starter allowed, must directly engage flywheel. No internal clutch type transmissions. Except auto automatics. You may run Brinn, Bert or Falcon transmissions are allowed but add 50lbs weight to the car.

AUTOMATIC: Must remain in OEM or OEM replacement case with a functioning OEM appearing pump. Must have an approved scatter shield. Scatter shield must be constructed of minimum of .125-inch by three-inch steel, 270 degrees around flex plate.

DRIVE SHAFT: Minimum two-inch diameter steel drive shaft & must be painted white. Steel slip-yokes only. 360-degree drive shaft loop required and must be constructed of at least .25-inch by two-inch steel, or one-inch tubing, mounted six inches back from front U-joint.

23. **ENGINE LOCATION:** Rear of engine (bell housing flange) must be mounted at least 72 inches forward from the centerline of rear axle. Engines offset must be kept within 2 inches of centerline of front cross member with engine level. Minimum 11-inch engine height from ground to center of crankshaft. Radiator must be mounted in front of engine. Cooling system may be modified. Overflow tubes must be directed to ground between frame rails.
24. **ENGINE SPECIFICATIONS:** Any American made engine allowed. Steel heads, block & oil pan only. All engines must be able to be used in conventional passenger car without alterations. Engine mounts cannot be removed or altered. **Castings and fittings must not be changed. Wet oiling system only. No Roller cams**
25. **The Chevrolet Performance Parts 602 engine (GM Part Number – 88958602) will be an option in 2018 (see G, below) All engines are to remain sealed from the factory. The original factory seals must remain unaltered, tampering, removal, modifications of any type and/or broken factory seals will not be permitted. (The Chevrolet Performance Parts 602 crate engine may have part number changes from time-to-time as issued by the manufacturer.) B.) One (1) four (4) barrel 650 cfm unaltered Holley carburetor, Part Number 4777 or 80777 or Holley HP Carburetor Part Number 80541-1, (-2) will be**

permitted. One (1) two (2) barrel unaltered 500 cfm Holley carburetor Part 4412 will be permitted. All carburetor components must remain unaltered. Any changes will result in disqualification from the event. Any alterations to the carburetor will not be permitted. C.) All engines and all components must remain in their original configuration and form as purchased and/or delivered from the factory. Any changes will result in disqualification from the event. Any alterations to the engine will not be permitted. D.) Any part that is sealed from the factory that has been tampered with and/or removed will result in an immediate penalty. The minimum penalty will be a \$1,000 fine, loss of all accumulated points for the year and a loss of all earned purse money for the event night. E.) Any issued penalty may include and will not be limited to a suspension of the car, driver, car owner, engine builder from participation in any S.F.C.R. event. F.) Any participant (driver, car owner and/or engine builder) that is found to have tampered with the engine will lose all points accumulated for the season, all earnings and the parts will be impounded for competitive analysis. In addition the participant may be suspended indefinitely from all S.F.C.R. events. G.) Changes and/or alteration to the engine, intake manifold, cylinder heads, valve covers, valve components, front cover, oil pan, harmonic balancer and/or any parts on or in the engine will not be permitted.

ALL GENERAL RULES APPLY

A- MODIFIED CLASS

Engine

1. Any American made push-rod type engine will be permitted as long as the rear engine bell housing flange is mounted at least 72"-inches forward from the center of the rear axle. The engine offset must remain within two (2") inches of the center line from the cross member. The minimum engine height when measured from the ground to the center of the crankshaft is 11" inches. Other engines of the push-rod type that meet criteria may be approved for competition.
2. All engines used in the competition must be able to be used in a conventional passenger car without alteration. Alteration of motor mounts will not be permitted. Alteration of the casting and/or fittings will not be permitted. Any machine work on the outside of the engines or machine work on the front or rear of the crankshaft will not be permitted.
3. Aluminum blocks will not be permitted.
4. Magnetos will not be permitted.
5. Wet sump oiling systems must be operative. Overall dry sump systems will not be permitted.
6. Alteration of the cooling system will be permitted. If alterations to the cooling system are made the stock-appearing hood line must be maintained.
7. The battery must be securely mounted and shielded. The battery must not be mounted inside the driver's cockpit.
8. The exhaust system) must be mounted with the exhaust directed away from the vehicle and/or away from the ground (preferably horizontal and outside the body of the car). A maximum of ½" inch clearance
9. Surrounding the header pipe when directed through the firewall on the driver's side. Local track rules will prevail when decibel and/or muffler rules.
10. One two or four barrel carburetor is required.
11. The engine must be a normally aspirated configuration.
12. Fuel injection systems or electric fuel pumps will not be permitted.

Transmission & Driveline

1. The drive shaft must be made from magnetic steel. The drive shaft must be painted white with the car number clearly labeled in the drive shaft.
2. Carbon fiber drive shafts are allowed
3. Aluminum, or fiberglass, shafts will not be permitted.
4. A ½" inch x 2" inch 18 gauge steel drive shaft hoop is mandatory. The drive shaft hoop must be at least six (6") inches behind the universal-joint. Two hoops are strongly recommended. A single 1/8" inch plate on the right side of the drive shaft tunnel is recommended. be securely-mounted (welded) roll cage tubing.
5. All competitors are encouraged to perform systematic checks on their drive-train.
5. Direct drives and/or any type devices will not be permitted.
6. The transmission must be bolted to the engine. All Cars must have forward and working reverse gears and be able to shift to forward or reverse with engine running.
7. Clutch-type transmissions must be equipped with explosion-proof steel bell housing. In lieu of an explosion-proof bell housing or if one is not available for your engine, a shield of at least ½" inch x 6" inches covering the clutch area 360 degrees securely fastened in place and fabricated from magnetic steel will be permitted.
8. The steering box must be O.E.M. any type rack and pinion style steering will not be permitted. The original bolt pattern that matched frame type must be used. In the cockpit, steering may be modified t suit the driver but must remain in the left side of the vehicle. Moving the steering mechanisms to the center of the vehicle will not be permitted.

Electronic Devices & Traction Control

1. All electronic and/or computerized wheel spin and/or acceleration retardation traction control devices will not be permitted. Controlled timing devices attached to or controlling accelerator or rotation of wheel will not be permitted. GPS and/or any other type of electronic tracking and/or device will not be permitted.
2. All traction control devices utilizing wheel sensors and/or any means of meas-

uring ground speed to control wheel spin will not be permitted.

3. Adjustable ping control services, dial a chip controls or automated throttle controls will not be permitted in cock pit or driver accessible area.
4. Adjustable restrictor plates will not be permitted.
5. Any remotely controlled components inside or outside the cock pit of any competitor's race car will not be permitted.
6. Radios or devices for transmitting voice or data will not be permitted, either in the racecar or on anyone connected with the car.
7. The uses of pit boards or colored flashlights are prohibited.

Fuel cells and Fuel

1. All cars must have fuel cells. The maximum capacity for the fuel cell will be 32 gallons. The fuel cell must be completely enclosed in an 18-gauge magnetic steel container. Aluminum fuel cell containers will not be permitted. All fuel cells must be completely visible. All fuel cells must have a minimum of 2"x2" inch x 1/8" inch steel straps surrounding them. The fuel cell must be protected in the rear of axle by securely-mounted (welded) roll cage tubing.
2. Any driver must be prepared to drain fuel upon request for measurement of the fuel cell.
3. The fuel cell must not extend lower than protective tubing.
2. Any driver must be prepared to drain fuel upon request for measurement of the fuel cell.
3. The fuel cell must not extend lower than protective tubing.
4. Racing gasoline or alcohol will be permitted.
5. Nitrous oxide, nitrous methane, propylene, oxide or any type of additives will not be permitted.
6. Fuel may be inspected at any time during any event.
7. All fuel cells must have valve in breather and filler check valve.

Roll Cage

1. All cars must have a roll cage. The roll cage must be approved prior to competition and it must be welded to the frame. The driver's head must not protrude above the top of the roll cage with the driver's helmet on. The top of the roll cage must extend above the top of the driver's helmet by a minimum of one (1) inch. The entire roll cage and all roll bar pieces must be fabricated from magnetic steel a minimum of .095" in thickness.
2. The driver and right side door bars must be parallel to the ground and located perpendicular to the driver. There must be right side door bars. The side bars must be welded to the front and rear of the roll cage. No brazing or soldering is permitted. The door bars must have a minimum thickness of .095" and must have a minimum of 1-½" diameter. On the driver's side there will be a minimum of three (3) door bars.
3. Foot protection is mandatory. One piece of magnetic steel tubing, a minimum .095" in thickness, must be fastened and/or welded across the back of the engine with vertical tubing a minimum of .095" thick.
4. The door side roll bars are mandatory and must extend into the door panels.
5. The roll cage must consist of continuous hoops that are no less than 1-½" in diameter and must have a minimum thickness of .095"
6. The roll cage must be mounted securely (welded) to the frame in a minimum of 6(six) places.
7. The roll cage must consist of a configuration of front and rear hoops connected by tubing on the sides and/or side hoops. Roll cage must be securely supported and braced. Gussets to brace any portion of the roll cage will be permitted.

Body

1. The front windshield and rear window support must be stock appearing. The front window support may have a clear lexan support of no more than 16" inches including the roof post at the bottom and going straight to the roof. The support must be securely fastened in a positive manner.
2. The front roof post must be in a straight line from the top to bottom.
3. The sides of the engine compartment will remain open. Any side panels in the engine compartment area will not be permitted. A five (5") inch drop on either side of the hood will be permitted and it must be enclosed at the rear of the

hood. The firewall on driver's side must meet the front of the door. The firewall must be a minimum of 16" - inches in length from top-to-bottom.

4. The top of the doors must remain in line with the rear engine plate. The bottom of the doors may extend a maximum of eight (8") inches past the motor plate toward the front of the vehicle. Any material that exceeded 8" inches will not be permitted.
5. A maximum of (1") inch flange for the purpose of strengthening only will be permitted on the front nose only. Side fins and/or flanges of any kind along the length of the entire car (hood, front, and/or roof) will not be permitted.
6. A maximum of one (1) stone deflector, for rear mounted oil pumps, oil filters, and for the main oil tank will be permitted. The deflector may be made of steel, aluminum, or heavy gauge wire. The cover may only be mounted near the unit it is designed to protect with a maximum size of eighteen (18"x18") inch square and mounted only from the upper right frame rail to the lower right frame rail.
7. The minimum roof height is 42" inches with a maximum height of 52" inches.
8. The minimum deck height is 28" inches with a maximum height of 38" inches.
9. All cars must have a car number on both sides and the roof that are at least 18" inches in height and 14" inches in width.
10. The driver's last name must be displayed under the car number in a legible font and is a minimum of eight (8") inches high letters.
11. A minimum of two (2") inches of tire clearance from the body is required.
12. The minimum ground clearance will be four (4") inches.
13. The measurement from the center of the hub to the rear top deck will be a minimum of 34" inches and a maximum of 48" inches.
14. The maximum body width at the body's widest part will be 72" inches. The minimum of width at the body's narrowest part will be 53" inches. The top of the doors may have a maximum width of 67" inches. The bottom of the doors may have a maximum width of 68" inches.
15. On the left side the rear of the door may flare out six (2") inches for tire clearance.
16. The bottom of the flare must be curved and rounded not pointed in any fashion.

17. The maximum rear width of car must be 67" inches at the widest point.
18. The maximum rood width will be 50" inches with a minimum of 44" inches.
19. The maximum rood length will be 56" inches with a minimum rood length of 41" inches.
20. The maximum height on rear roof post vertical is 5" inches.
21. The nose piece must not exceed 45" inches in width, centered between the frame rails and must not extend past the leading edge of the front bumper. The nose piece must have a minimum of six (6") inches from the ground to the bottom edge of the nose piece.
22. The composite, Dominator 2012 "Modified Nose" is the only approved composite "Modified Nose" for competition. To be eligible for competition the Dominator 2012 "modified nose" must meet all manufacturer specifications.
23. No spoilers are allowed.

Interior and Driver Compartment

1. All windows must have a minimum 11"-inches vertical opening. The entire interior must have a minimum of 11" inches of clearance from the interior deck to the roof and all sections of the roll cage. The minimum window opening will be 12" inches. The interior deck sheet metal to the right side of the driver from the back of the seat forward should be fabricated on an angle from the drive shaft tunnel to the right side window to promote ease of exit for the driver through the right side and or front window opening.
2. **ALL CARS MUST HAVE A WINDOW NET OR USE ARM RESTRAINTS and at least 3 vertical bars in front of the driver.**
3. A master ignition switch within easy reach of the driver is mandatory. The switch must be clearly labeled "ON" and "OFF"
4. Hydraulic and or pneumatic weight jacks, trackers, or similar adjustable components of any type will not be permitted.
5. Mirrors of any type will not be permitted.
6. The rock guard should end at a point perpendicular to the steering wheel.
7. The drivers compartment must be sealed from the engine and the race track. The rear bubble of the hood should be closed and sealed from the driver.

8. The maximum slope/rake of the interior sheet metal "shell" front to rear is 4" inches when measured from the firewall to the base of the spoiler. A maximum of 2" inches of the slope/rake will be permitted in front of the rear of the seat to the firewall and a maximum of 2" inches of slope/rake will be permitted from the rear of the seat to the base of the spoiler.
9. The top of the interior must be flush with the top of door and quarter panels.
10. Any car in competition must have right side door bars as part of the roll cage. Please reference 15.-10 B in the roll cage section.

Roof & Roof Supports

1. All roofs must be full size. Half moon roofs will not be permitted. The roof must be mounted no more than 12" (twelve inches) past the rear axle.
2. Wings, roof spoilers or ground effects of any kind will not be permitted.
3. All flat type roofs will be allowed a maximum 3" inches difference in height between the front of the roof and the rear of the roof. This measurement may be taken from the interior and/or the ground up in any circumstance. The rear of the roof must maintain the same height from side to side.
4. All curved type roofs will be allowed a maximum of 5" inches in the front and 2" inches in the rear. The break in the roof must be within 6" inches from the center of the roof.
5. Wedge roofs will not be permitted.
6. Dished roofs will not be permitted. Roofs must be rounded side to side. Bead rolls will be permitted.
7. The rear roof post must begin where it meets the back edge of the roof. The rear roof supports may not extend pass the front side of rear upright of the roll cage.
8. The side vents on the front roof posts may extend rear ward from the lowest points, a maximum of 16" inches, then at a 90 degree angle to roof for one (1) configuration, side vents must meet the outside of the car.
9. The roof side (sail) panel window size must be 10" inches x 15" inches and must match drawing number 2 side view. There will be a tolerance of 2" inches at the top and 3" inches at the bottom. A maximum crown of two (2) inches will be permitted, measured from the center of a common tangent

point on either side of the crown.

10. If the long roof side (sail) panel is being used there will be no radius.
11. Any sun shield must be on hinge for easy exiting, taping will not be permitted. The window opening must remain at a minimum of 12" inches.
12. All race cars in competition must meet the measurements illustrated in the dirt car drawing.
13. There are only (4) four approved roof supports to choose from.
14. The roof should be single thickness of material. The roll bar hoops must be exposed for inspection.
15. If the roof is curved then a level will be places on the top of the car and if the roof is 5" inches or less in the front and 2" inches or less in the rear and the break is in the middle then the roof will be permitted.
16. The roofs on these cars will be stock appearing. If a Dirt car and/or local track official determines the roof does not meet the requirements as stated above then a penalty as determined by the official may be determined prior to competition, additional weight and/or other penalties, unless the roof can be returned to within the parameter as stated above prior to competition in the event that the roof was inspected for.

Suspension

1. Any "live axle" type rear ends will not be permitted.
2. Quick change rear ends will be permitted. Only magnetic steel tubes will be permitted.
3. Aluminum birdcages will not be permitted.
4. Independent rear suspension will not be permitted.
5. Only floater hub assemblies will be permitted.
6. The front suspension must be O.E.M. and be in stock location. The front suspension must have replacement stock part) from the same type of suspension **from** the OEM Manufacturer, The bolt used for weight jacking purposes must be with in 1" inch on the original spring centerline.
7. Aluminum spools will be permitted.

8. Steel coil-over eliminators and/or steel/aluminum coil-over kits will be permitted. The coil-over eliminators and/or coil-over kits must conform to the shock and spring rules. In the rear of the car a minimum of 5" inch spring is required.
9. All springs must have a tethered and/or cable system in place to securely fasten them in position in the car.
10. Aluminum shocks, shells, aluminum hubs, aluminum A-frames, aluminum rear end, aluminum tubes and/or aluminum suspension parts will not be permitted.
11. Only steel body, one piece non-adjustable shocks will be permitted. Adjustable shocks, including cockpit adjusters will not be permitted.
12. Coils over shocks of any type in the front of the car will not be permitted.
13. Only one shock per wheel will be permitted. Lay down shocks less than 12" inches away from brake rotor will not be permitted. Additional shocks in other locations will be permitted.
14. Only stock passenger car spindles will be permitted. Fabricated spindles will not be permitted.
15. Alterations and/or relocation of the lower A-frames will not be permitted. Dirt car approved after market lower control arms, which are mounted in the OEM location and maintaining the OEM Manufacturer will be permitted.
16. Tubular type upper A-frames will be permitted. The upper A-frame mounting locations may be altered. Aluminum cross shafts will be permitted.
17. Composite leaf springs will be permitted.
18. Aluminum shackles will be permitted.

Brakes

1. All cars must be equipped with a working braking system on all four wheels and all four wheels must be able to stop/brake at all times.
2. Only magnetic steel rotors will be permitted. Carbon fiber and/or aluminum rotors will not be permitted. Drilling, lightening and/or any alteration to the brake rotors or calipers will not be permitted.
3. Only stock O.E.M. and/or Dirt car approved aftermarket calipers will be per-

mitted. Only the Wilwood P/N/ #120-7197 is Dirt car approved.

4. Only stock O.E.M. rotors will be permitted. Single disc brake rotors or scalloped rotors will not be permitted.

Wheel and Tires

The tire rule may be amended by bulletin.

1. Note: The 2018 regular track season will introduce M-30S and M-60, with a redesigned tread pattern. The A-40S and the M-30S will be the only approved tires. The H40 and M-60is approved as a right rear option. Grooving and siping will NOT be permitted on the M-30S. Siping is permitted on the H40, and the M-60.

4. Recapping of an approved tire is not permitted.
5. Any local track official can confiscate any tire at any time and during any event to be evaluated and analyzed including verification using a tire durometer. Tires may also be submitted for further chemical analysis.
6. Defacing or altering any of the manufacture's identification markings, letter, words, numbers, on any tire will not be permitted. The tire compounds may be covered by duct tape as long as the local track and/or dirt car officials are able to remove the covering at any time for inspection purposes. Any alteration of tires may result in immediate suspension from all dirt car racetracks and/or events an/or penalties deemed appropriate by local track and.
7. Tire softeners and/or chemicals designed to alter the chemical characteristics of the tire and/or the tire surface will not be permitted.
8. **Mud plugs will be permitted on all four wheels.** Bead locks will be permitted on the right side only. The mud plug must have the car number on it. Only 8-inch Dirt car approved and labeled racing wheels will be permitted.
9. All wheels must be conventional one-piece magnetic steel and must be mounted with lug nuts. Aluminum, plastic and/or carbon fiber wheels will not be permitted.
10. All wheels must be fastened to the hub with five lug nuts.

Chassis/Frame

1. Only factory production full 1950 or newer parallel American passenger car frames will be permitted. The frame must be complete in front of firewall. Cutting of the frame in any way in front of firewall will not be permitted.
2. The frame must remain unaltered and must be meet the requirements of the attached drawing.
3. The right side frame rail may not be altered and/or raised and/or moved from the stock OEM location in any manner and must measure a maximum of six (6) inches from the ground to the bottom or lowest edge of the frame rail.
4. The front cross member may be notched to allow clearance for the radiator only. The cross member must be plated to retain complete box configuration.
5. Jeep, Bronco, 4-wheel drive, front wheel drive or sports car frames will not be permitted.
6. The minimum wheelbase permitted will be 108" inches. The maximum wheelbase permitted will be 112" inches.
7. Fiberglass lift bars and/or rear torsion bars will not be permitted.
8. Any frame may not be widened or narrowed and must be able to support the roll cage on both sides and must be full and complete on both sides.
9. The minimum frame and body height from ground is four (4) inches.
10. The front bumper must be mounted to the ends of the frame with the bottom loop parallel to the ground.
11. A minimum of 1" diameter tubing and/or pipe is required to for towing of the vehicle.
12. The rear bumpers must be constructed of tubing and/or flat stock. All rear bumpers and/or tubing utilized in the fabrication of the rear bumper assembly must have an end cap. The rear bumpers must protect the fuel cell.
13. The bumper) (front and rear) when measured from their center) must have a minimum of 25" inches of ground clearance. There will be a two (2) inch tolerance plus or minus regarding this dimension. The rear bumper and/or the nerf bars must not extend beyond the width of rear tires. All bumpers must have round edges. Sharp edges on any bumper and/or bumper surface will not be permitted.

14. The brace bars forward of the roll cage must not extend higher than stock hood height.
15. The rear push bars must not extend beyond six (6") inches of the rear quarter panel).
16. All side bars and bumpers must be capped on ends.
17. The maximum overall width of the car, front and/or rear, shall not exceed 78" inches when measured from the outside of the tire tread on both sides of the vehicle. A maximum on (1") inch spacer between the hub and wheel will be permitted. Steel and/or aluminum spacers will be permitted, provided the overall tread width of the vehicle does not exceed 78" inches.

Weight

1. All added weight) must be painted white with the car number clearly labeled on each weight.
2. All added weight) must be securely mounted to the car with minimum of two (2) ½ inch bolts that pass completely through each weight and the car. Weights that are mounted on the rear bumper or outside the body of the car will not be permitted. All added weight must be mounted below all windows and the interior sheet metal.
3. Any car that loses any weight during any event may be fined up to \$500.00
4. The minimum weight of car with driver at all times including after the race is 2,400lbs.
5. All weight determinations will be measured on the scales selected by the local track officials for each race event. Burn off and/or weight percentages and/or tolerance after the completion of any racing event will not be permitted.

General

1. It is the sole responsibility of each competitor for the effectiveness and proper installation, per the manufacturer's specifications to be adequate for competition at every event. Each competitor is expected to investigate and educate themselves for continuing improvement regarding their own personal safety equipment.

Seat belt/Restraint System.

1. Each car should be equipped with an SFI 16.5 or SFI 16.1 approved seat belt

restraint system until the date of the belt expiration (usually three years) Seat belt restraint systems shall be installed in accordance with the directions and application of the system supplier or manufacture.

2. Seat belt webbing that comes into contact with any sharp metal edge should be protected from the edge by means of push on grip vinyl trim. Seat manufactures supply the seat with trim protecting the webbing from abrasion or cutting under impact conditions and should be used to their specifications.
3. It is the responsibility of the driver, not the Officials or the Promoter to ensure that his/her seat belt restraint system and all components are SFI approved, correctly installed, maintained and properly used.

Protective Clothing

1. Each driver should wear a fire resistant uniform meeting SFI 3.2A/5 specification and display a valid SFI 3.2A/5 label.
2. Each driver should also wear fire resistant accessories that effectively cover the remaining parts of the body. Shoes and gloves should meet the SFI 3.3 specifications and display a valid SFI 3 label.

Seats

1. An aluminum seat built specifically for the purpose of the competition in auto-racing events will be required.
2. High back aluminum (stockcar style) seats should be securely mounted to the frame as recommended/required by seat manufacturer and chassis manufacturer.
3. Head rest (behind the head) should include padding. All areas surrounding the head should have padding.
4. A right head net or support is required. Head nets must be equipped with quick release mechanism.
5. The seat must be mounted a minimum of 30" inches from the center of the rear end, measured at the bottom of the seat.

Helmets

1. Driver should wear a full face helmet, with at least a valid SA 2005 Standard Snell and/or a valid SFI 31.1, SFI 31.2 or SFI 31.1 2000 label.
2. The driver should wear the helmet in accordance with the directions provid-

ed by the helmet manufacture and/or supplier.

3. If a head and neck restraint system is connected it should conform to the manufactures mounting instructions.
4. Head and neck restraints are strongly recommended.

Other

1. No sharp or protruding edges in or around the cockpit which would impede the driver's rapid exit from the car.
2. Windshield screens with a minimum of .090 inch screen must be securely fastened. Three windshield bars in front of the driver are recommended.
3. An electrical engine shut off switch is required. The switch must be clearly labeled and within the reach of the driver.
4. A fuel shut off valve is required. The valve must clearly labeled and within reach of the driver.
5. Flame retardant seat, roll bar, knee and steering pads or padding are recommended.

ALL GENERAL RULES APPLY

SPRINTS

1. Right rear tire must be a Hoosier ASCS medium 16 inch wide tire. Left rear tires must be an H-series compound 12 or harder. Front tires can be any Hoosier tire. Tires will be available at track.
2. Track tires will be checked, if caught with illegal tires, driver will lose points and money for that race.
3. All drivers should be in line and ready to go before their race session. The race will not be held up for you.
4. **All sprints are required to have a flat top wing with up to a 2 inch wicker bill or a dish wing with no wicker bill.**
5. **Torsion arm stop retainers are MANDATORY**
6. **Kingpin Tethers are MANDATORY. Must be C&R or butlerbuilt brand. Anyone showing up to race without a tether will have 14 calendar days to get one installed. Tethers are MANDATORY on all special races and the 14 calendar day rule does not apply to special show.**
7. **Front axle tethers will be recommended in 2018.**
8. **ALL CARS MUST HAVE A WINDOW NET OR USE ARM RESTRAINTS** and at least 3 vertical bars in front of the driver.

ALL GENERAL RULES APPLY

2017 Track Champions:

Sprints -Joey Montgomery

A-Modified - Billy Smith

B - Modified - Shane Blair

Super streets - Jason neel